









Monthly Operating Report

January: 2020

So. Sangamon
Water Commission
February 18th, 2020



# **TABLE OF CONTENTS**

SEC	CTION		PAGE NO.
Exe	ecutive	Summary	ES-1
1.	SAFE	ТҮ	1-1
	1.1 1.2 1.3 1.4	Safety Training Lost time Accidents Safety Audit Miscellaneous Safety	1-1 1-1
2.	COMP	PLIANCE, FLOWS AND LOADINGS	2-2
	2.1 2.2 2.3 2.4	Compliance	2-2
3.	OPER	ATIONS	3-1
	3.1 3.2 3.3 3.4	Events impacting operations  Emergency & Service calls  Emergency Call-outs  Customer Inquiries	3-1 3-1
4.	MAIN	FENANCE AND REPAIR	4-7
	4.1 4.2	Preventative and predictive maintenance Corrective repairs	
5.	PROJ	ECT MANAGEMENT & SUPPORT	5-1
	5.1 5.2 5.3	Staffing & Training Corporate Support Budget	5.2
6.	CAPIT	AL PLANNING	6-1
	6.1 6.2	Approved CIP Projects Current status	

# LIST OF TABLES

TABLE	PAGE NO.
Table 2.2 Influent Concentrations and Flow	2-2
Table 2.3 Finished Water Quality	2-2
Table 2.4 Weekly Grab Sample Analysis Results	2-4
Table 4.1 Budget Table	5-3

# **EXECUTIVE SUMMARY**

**Safety.** Safety is the number one priority at South Sangamon. We have instituted a monthly safety meeting for operations staff at the plant. There were no lost time accidents in the month of January 2020.

**Compliance.** The finished water quality was within regulatory limits and all reporting and sampling requirements were met for the month. A copy of the Operations Report submitted to the Illinois Environmental Protection Agency is available at **www.sswc.us**.

During the month of January 2020, the plant pumped 39.6 million gallons from the well field and 31.2 million gallons of finished water. This is 1.296 million gallons more than January of 2019.

The SSWC plant has been placed on Critical Review status. Systems on Critical Review will be evaluated for sufficient capacity before issuance of water main extension permits.

**Operations.** There was 1 emergency call-outs for the month. There was 1 customer inquiry for the month.

**Maintenance and Repair.** For the month of January 2020, there were 31 inspections, 3 preventative and 3 corrective maintenance activity completed.

**Budget.** Passed at May 20<sup>th</sup> 2019 meeting.

#### Capital Planning.

**Pigging Project** 

**Chloramines Project** 

New Berlin Meter relocation.

# 1. SAFETY

# 1.1 SAFETY TRAINING

At South Sangamon we strive to provide a safe working environment for all employees. This is accomplished with daily safety meetings and open communication.

# 1.2 LOST TIME ACCIDENTS

There were 0 lost time accidents in the month of January 2020.

# 1.3 SAFETY AUDIT

No safety audits to date.

# 1.4 MISCELLANEOUS SAFETY

No usable Fall Arrestors for aerator on premises

# 2. COMPLIANCE, FLOWS AND LOADINGS

#### 2.1 COMPLIANCE

The finished water quality was within regulatory limits and all Bacteriological testing was completed for the month of January. A copy of the Operations Report to the Illinois Environmental Protection Agency (IEPA) is available on the SSWC website.

# 2.2 INFLUENT FLOWS AND LOADINGS

The total gallons pumped from the well field were 39.558 MG. The influent parameters were all within the normal range.

The influent flow and loadings are summarized below in Table 2.2

		Tab	le 2.2 Infl	uent Conce	entrations a	nd Flow		
	рН	Temp	Iron	Manganese	Fluoride	Hardness	Alkalinity	Well Flow Gals (MGD).
Max.	7.70	16.6	1.92	.252	-	370	300	1.45
Min.	7.50	14.1	.10	.177	ı	345	280	1.138
Avg.	7.62	15.3	.98	.213	-	355	287	1.261
Total	1	-	1	-	1	-	-	39.1

#### 2.3 EFFLUENT CONCENTRATIONS

The facility filtered 35.59 MG during the month with a daily average of 1.276 MG and a min/max .952/1.288 MG.

				Table	2.3 Fir	nished Wat	er Qualit	у		
	Free CL2	Total CL2	рН	Temp	Iron	Manganese	Fluoride	Hardness	Alkalinity	Phosphate
Max.	1.8	1.9	8.20		0.04	0.039	0.89	380	300	2.33
Min.	1.3	1.4	8.00		0.01	0.001	0.35	100	240	1.05
Avg.	1.6	1.7	8.13		0.02	0.015	0.68	135	282	1.78
MCL	-	-	ı	ı	1.00	ı	4.00	-	-	1
SMCL	-	-	-	-	0.30	0.050	2.00	-	-	-

# Finished Water Flow Comparison for FY 2019-20

Time Period	2018-2019	2017-2018	2016-2017
Feb 2019-Jan 2020	380,970,204	401,431,013	393,063,344
Increase for the same per	iod last year	-20.461 MG	

		FINISHED WA	TER PUMPING	G HISTORY		
	2019-20	2018-19	2017-18	2016-17	2015-16	2014-15
Feb	28,625,431	25,617,914	27,373,232	26,095,228	26,336,077	28,745,378
March	31,237,000	28,217,699	30,068,363	27,851,811	28,729,919	31,217,486
April	28,418,249	27,110,578	29,625,797	29,292,618	29,270,184	31,690,073
May	33,045,927	33,304,196	32,120,873	33,349,391	33,371,016	31,157,411
June	33,460,303	34,040,000	39,931,402	41,541,321	31,092,539	38,462,951
July	23,742,374	41,178,722	42,164,927	35,378,396	33,123,375	38,674,894
Aug	25,018,633	35,176,238	38,760,634	35,401,490	38,109,133	33,748,543
Sept	34,234,782	34,754,000	39,896,986	36,325,215	36,546,171	29,763,075
Oct	30,769,238	30,353,482	33,506,605	34,374,820	34,783,455	28,803,052
Nov	30,877,400	30,464,000	28,617,333	30,478,309	27,217,293	28,426,579
Dec	29,703,954	31,930,000	28,808,037	32,525,530	27,788,637	28,656,869
Jan	30,073,516	28,823,375	30,556,824	30,449,215	28,510,121	30,346,721
Totals	359,206,807	380,970,204	401,431,013	393,063,344	374,877,920	379,693,032
Avg	.984 MGD	1.04 MGD	1.10 MGD	1.07 MGD	1.03 MGD	1.04 MGD

# 2.4 LAGOON DISCHARGE CONCENTRATIONS

The results for the NPDES lagoon discharge permit are summarized below.

Table 2.4 Weekly Grab Sample Analysis Results

	ı	_agoon Eff	luent Results	;		
Date	Fe (mg/l)	Mn (mg/l)	Chloride (mg/l)	Cl <sup>2</sup> (mg/l)	pH (S.U.)	TSS (mg/l)
January 2 <sup>nd</sup> , 2020	.14	.18	210	0	8.2	<4
Minimum	.14	.18	210	0	8.2	<4
Maximum	.14	.18	210	0	8.2	<4
Average	.14	.18	210	0	8.2	<4
Monthly Avg Limit	2.000	1.000				15
Daily Limit	4.000	2.000	500	0.05	6.0-9.0	30

The Chloride sample for the month, performed by the Springfield Metropolitan Sanitary District, was below 30,000 mg/l for the month of January 2020. The limit for chloride discharge to the sanitary district is 30,000 mg/L.

# 3. OPERATIONS

# 3.1 EVENTS IMPACTING OPERATIONS

There were no incidents impacting plant operations for the month of January.

#### 3.2 EMERGENCY & SERVICE CALLS

# **Service Calls:**

• There were 0 emergency call outs for the month.

# 3.3 EMERGENCY CALL-OUTS

There was 1 emergency call-out for the month requiring operational personnel at the plant after normal business hours

# 3.4 CUSTOMER INQUIRIE

There was 1 customer inquiry.

#### OTHER WORK PERFORMED

Learned correct operating procedures for the new filter train Trouble shooting of new train Trouble shooting of CIP skid and CIP procedure Repaired chlorination system Repaired air purge valve at Vigil Rd



Air purge drain line near Vigil Rd and New City Rd. on January 26<sup>th</sup> the valve stuck open requiring plant personnel to go to this location and close the valve.




Air purge valve ring had been damaged and the pit lid is missing.



Upon closer inspection, the pit lid was found to be in the pit.



Current pigging station pit lid that is slated to be replaced.



Loellke sent a new pit lid (interpretation of said new lid door). This lid also would not work due to location of hatch and height restrictions.

# 4. MAINTENANCE AND REPAIR

# 4.1 PREVENTATIVE AND PREDICTIVE MAINTENANCE

For the month of January 2020, there were 31 inspections, 3 preventative and 3 corrective maintenance activity completed.

# 4.2 CORRECTIVE REPAIR

Pulling and cleaning pre filters on all 3 filter trains on weekly basis

CIP train 1,2 and 3

Drained brine tank 1 and cleaned it out.

Drained brine tank 2 and inspected. Will Clean it out in the spring.

# 5. PROJECT MANAGEMENT & SUPPORT

# 5.1 STAFFING & TRAINING

- With the addition of a new staff member training has been continuous and ongoing.
- Operator and Asst. Operator have been studying for EPA licensing test.

# 5.2 OPERATIONAL SUPPORT

The following individuals, either on-site or remotely, provided assistance in operation and/or maintenance of the plant during the month of January 2020.

- Kevin Canham
- Stephen Bivin
- Katie Krall
- Keslee Carson (Westech)



# 5.3 BUDGET

Table 5.3 Operating Budget

Table 5.3 Budget Table

Budget Category	Month Budget	Month Actual	YTD Budget	YTD Actual	Annual Budget
Labor (D.L. + OH)	\$13,909.06	?	\$68237	\$70128	\$163,768
Utilities	\$8,306.30		\$40,750	\$36,019	\$97,800
Chemicals	\$22,421		\$110,000	\$74,593	\$264,000
Maintenance & Repair	\$13,668.62		\$67,056	\$56,429	\$160,937*
Chloride	\$13,160		\$65,800	\$58,080	\$157,920
Lab Supplies and Equipment	\$1,918.09		\$9,410	\$5,987	\$22,584
Office Supplies	\$220.14		\$1080	\$627	\$2,592
Miscellaneous Expenses*	\$41		\$123	?	\$500
Other Operating Costs	\$1398	?	\$6990	\$6107	\$16,776
Engineering Fees	\$2,500		\$7500	\$5950	\$30,000
Office Equipment rental	\$65		\$542	\$325	\$780
Locates	\$378	0	\$1890	`\$2,758	\$4536
Truck	\$3,333	0	\$33,333	\$35,560	\$40,000
Total	\$81,318.21	\$37337.12	\$377,488	\$349,805	\$962193

\*as of September 30 2019

# 6. CAPITAL PLANNING

# 6.1 APPROVED CIP PROJECTS CURRENT STATUS

Chloramine conversion project- Hach arrived to commission analyzer. Mother board was damaged causing a fatal error to the equipment. Hach will commence startup of Monochloramine analyzer in February after parts arrive and repairs have been made.

New Berlin Meter master meter relocation project is commencing. Engineering and relocation plans have been finalized. Awaiting ground breaking.

# 6.2 DRAFT CAPITAL IMPROVEMENT PLAN

The CIP is a planning document that includes all projects anticipated to exceed \$5,000 in cost over the next five years. The CIP is an ongoing process and will be refined from time to time as projects are completed and new issues are identified.



											e contill	Canya	ווסוו זיימיב	5 5	200	<u>-</u>	South Sangamon Water Commission - IL 1670080					L						
													od Inc	Jailual y 2020	2												Dad	Page 1 of 2
		Pilm	Pumning Totals								Chemic	Chemicals Applied							╢	IIF Filhers					Softeners	ي	g*	5
	Raw		<u> </u>		Lagoon	Sodium Permanganate	Sodium manganate	Sodium Bisulfite BW		Sodium Hypochlorite	e Am	Ammonium Sulfate	Fluorosilicic		Phosphate	So Bisulfi	Sodium Bisuffite Pond	로	Hours since previous backwash	orevious sh	Wash	Water	Water		Each dav indicate total number of	ed unmpe		Regeneration
Time:	-	_	_	오	Effluent			Am't	$\vdash$	$\vdash$	$\vdash$	$\vdash$	$\vdash$	-	$\vdash$	-	$\vdash$				Water	47			hours since previous regeneration.	s regenera	-	=
Date Meter	Ran (Mgal)	1. Filtered	(Mgal)	Pumpage (Mgal)	(Maal)	Used lbs.	Calc	Used lbs.	calc Used	ad Calc	Used	Calc mo/l	Used Calc	lc Used	ag Carc	Used lbs.	Calc		Bank #		(Maal)	(Maal)	(Maal)	_	If regeneration at mid-day, indicate	id-day, indi	_	Used Water
	_	_	_	_	_		NaMnO4	i	+	+	+	- 10	+	+	- 60		b	-	2	3		_	-	1	2	3		+
1 7:00		1.116 0.952				20		0			80	0.00		0.62	9 0.4			99'0	99'0	99'0	0)(			30	42.0	44.0	41.0 68	1
2 7:00	Ш	1.355 1.272				21		0		180 2.	2.12	0.00		0.48	9 0.31		12.91	99'0	99'0	99'0	0.0			11 69.0		33.0	45	4562 21700
						20	0.39	0			2.36	00:00						99:0	99:0	99:0	0.0			37 28.0	52.0		42.0 68	
	_				_	21		0		190 2.9	2.59	0000						99'0	99:0	99.0	0.0			31		39.0		+
2 7:00	14.4 1.2	1.203 1.083	3 0.007	0.967	0.084	23	3 0.46	0 0			2.70	0000	27 0	0.64	49 2.0	1 24	13.64	990	990	99.0	6 6	0.070 0.708	0.708 0.375	75 67.0	40.0	34.0	38.0 68	6843 3255(
	┸	┸	┸			3 8		> <			36	000					-	0.00	0.00	0.00	5 2					30.0	- 1	+
00:7				0.886	0.070	18	0.38	0		159 22	2.33	0000	22 22	0.57	1 0.04	4 16		990	0.00	99.0	5 0		0.669 0.355		46.0	0.00	43.0 45	4562 21
1	┸					24		0			2.50	0000		0.59	6 02			99'0	99:0	99.0	6			0.6 45.0		39.0		5843 32
			1			17	1	0			59	0000		1.53				99'0	99.0	99.0	0				43.0	35.0		6843 32
11 7:00		1.372 1.226	11000 9	1 1.042		25		٥		195 2.3	2.38	0.00	36 (	0.57	8 0.3	0 34	18.12	99'0	99'0	99'0	0.0	0.085 0.801		25			40.0 2281	81 10850
12 7:00	15.7 1.3	1.348 1.202	12 0.003	1.143		25		0			47	0000		0.56	11 0.3		13.55	99'0	99'0	99'0	0.0	0.073 0.7	0.786 0.416	16 48.0	45.0	37.0	32.0 91	9124 43400
13 7:00	16.9	1.432 1.288	18 0.014	4 1.160				0			25	0.00	26 (	0.51	9 0.3	1 25	12.76	99'0	99'0	99'0	0'0	0.084 0.8	0.842 0.446			34.0	45	4562 21700
14 7:00	16.7 1.391			0.975				0			42	0.00		0.56	9 0.3			99'0	99'0	99'0	0.0	0.075 0.811		30	36.0		45.0 45	4562 21700
								0			42	00:00						99'0	99'0	99.0	0.0				45.0	39.0		
								0			33	0000 0						99'0	99'0	99:0	0.0					36.0	39.0 68	-
17 7:00	13.5 1.1	1,329 1,194	10.011	1 0.994	0.083	12	0.38	0	0.00		2.10	0000	21 23		30 1.27	7 31	18.13	0.66	0.66	99:0	0 0	0.072 0.690		16 26.0	44.0	43.0	37.0 45	4562 21700 4562 21700
	┖							0		232 3.	22	00'0		0.78				99'0	99'0	99'0	0.0		07 0.374	74	33.0			+
_						13		0			73	00.0					7	99'0	99'0	99:0	)0			75		38.0		81 10850
21 7:00	Ш	1.196	10004		ш	19		0	П		43	00.00			52 2.0			99.0	99.0	99:0	0.0	0.072 0.782		П	26.0	37.0	40.0	9124 43400
						23		0		180 2.	45	00.00		0.55	2 0.0			0.66	99:0	99.0	0)(		21 0.382					$\dashv$
	_	_		- 1	_	20		0			19	00.00		0.54	5 0.20	17		99.0	99.0	99.0	);				48.0	43.0	- 1	9124 43400
24 7:00	136 1134	1.341 1.184	0.015	5 1.028	0.090	20		0		165 27	2.09	0000	25 24	0.53	6 0.27	14	0.00	0.66	0.66	990	0 0	0.080 0.774	0.410	23.0	0.44.0	46.0	40.0 4562	4562 21
_	L		L	┸		21		0			255	000		061	L		Ľ	990	0.66	0.66	Ö			51 46.0			43.0 45	4562 21
	1	1_						0			35	00:0		1.58	8 0.2			99'0	99'0	99'0	0.0				45.0	45.0		6843 32550
28 7:00		1.382 1.248				20		0			2.02	0.00		0.53	9 0.36		1	99'0	99'0	99:0	0.0			32 51.0			22	2281 10850
						23		0			2.57	0.00						99'0	99'0	99:0	0)				48.0	37.0	40.0 68	
30 7:00				1.013	0.102	24		0	0.00	179 2.	2.32	00:00			17 0.66			99:0	99:0	99:0	); ;		57 0.401	01 41.0		36.0		4562 21700
31 7:00						77		0 1	П	П	32	0000						O.00	Orop	0.00	ö							
Total	.,	٠,				99		0	0 26	-	20	0.00			7		m .	:				`	`			731		163232 78120
Ave.						21.3		0	0 0		2.37	000				2		99.0	99'0		#DIWOI 0.0					38.5		
Max						27.0		0			3.22				52 2.01	1 90	7	99'0	99'0	99'0	0 0					46.0		1
Win	12.7 1.1	1.116 0.952	0.000	0.886	0.070	13.0	0.22	0	0	144	1.73	00:00	21 (	0.44	1 0.04		0.00	99:0	99:0	99.0	0	0.059 0.6	0.622 0.264	34 23.0	33.0	33.0	32.0	2281 1085
1 20 %	% Sodium Permanganate	andanate		Pre-aerator	5		CHLORINA	NATION		$\bot$	$\downarrow$		FLUORIDATION	1	$\downarrow$				certifythat the information in this report is complete	ne informatio	in in this rec	ort is comp	gto					-
	% BisulfiteSolution	ion	L	Membran	Membrane Backwash	Æ				-	-				L	L			and accurate to the best of my knowledge	to the best	of m y knowl	adge.				H	H	H
12.5	% Sodium Hypochlorite Solution	chlorite Sol	ution	Post Softener	aner		Type of Ch	Chlorine Used		Sodium Hypochlorite 12.5 %	orite 12.5	%	Type of Fluoride Used	e Used	Hydroffu	Hydrofluosilicic Acid 19% F	id 19% F		Reported by:				Minois C	Illinois Operator Certification II	ification IC			Н
4 20%	% Ammonium Sulfate Solution % Ellippesition Acid Solution	ulfate Solu	ų į	Post Softener	ener		Chloring	Il andonico	Analyzare Head-Hack C1 47 (9) & 6500ec	7 (2) 8, 55/	2062	-	Eliocida Analyzar I lead: Hach 2000 SBADNS method	- Ileodir	2 000 do	DADMS m.	poge		Date:	ŀ	L	+	1			+	+	+
33	% Phosphate Solution	Jution		Post Clearwell	Irwell		5	o contraction in	200.1801	6	200		acino and	200	10077		3		Date Bacterials Ser	als Ser							H	H
40	% BisulfiteSolution	ion		Lagoon Effluent	Hinent						L			L	L				-		ŀ	L	ļ		ŀ			ŀ

South Sangamon Water Commission - IL 1670080
5
Total Total Total Total Turbidity Total Total Soluble Total T
Hard. Fe Mn
11.9r
155 0.72 0.214 0.326 0.062
14.7 280 350 0.78 0.214
355 0.67 0.221 0.336 0.041
14.7 280 350 0.95 0228 0.339 0.051
14.6 280 358 1.95 0.250 0.325 0.037
14.7 300 360 0.70 0.223 0.313 0.043 0.042
15.4 290 350 0.59 0.216 0.340 0.042 0.030
290 354 1.36 0.220 0.316
15.6 280 350 0.82 0.22 0.343 0.032
16.1 280 352 0.87 0.212 0.347 0.037 0.038
14.9 286 350 0.79 0.216 0.330 0.038 0.033
15.5 282 352 0.87 0.241 0.332 0.067 0.054
7.70 14.7 300 350 0.70 0.223 0.313 0.343 0.344 0.33 770 15.4 200 350 0.74 0.33
14.3         290         354         1.36         0.220         0.316         0.017         0.023
15.6 280 350 0.82 0222 0.343 0.032
280 352 0.87 0.212 0.347 0.037
14.9 286 350 0.79 0.216 0.330 0.038
15.5 282 352 0.87 0.241 0.332 0.067
13.8 280 360 1.96 0.313 0.235 0.209
7.70 14.1 282 365 1.55 0.271 0.388 0.174 0.144 780 13.0 285 358 114 0.204 0.100
146 285 350 1.94 0.321 0.328 0.132
14.3 290 350 1.17 0.261 0.298 0.149
14.6 290 356 0.70 0.235 0.295 0.131
285 352 0.82 0.238
14.2 280 360 0.75 0.260 0.336 0.111
280 355 0.95 0.258
850 850 1470 750 050 050 050 050 050 050 050 050 0
14.2 250 350 0.50 0.20 0.20 0.30 0.30 0.30 0.30 0.30 0.3
14.3 290 350 1.04 0.246 0.359 0.038
14.7 285 354 1.00 0.239 #DIVIDI #DIVIDI 0.331 0.071 #DIVIDI
16.1 300 365 1.96 0.321 0.00 0.00 0.388 0.209 0.00
7.60 13.8 280 350 0.59 0.212 0.00 0.00 0.235 0.017 0.00 0.023
Lagoon Effluent Tests pH Temp TChlor Mn Fe Chloiride TSS
°C mg/l mg/l mg/L
0 0.18 0.14 210

